



1 PERSPECTIVE - SOUTHWEST



2 PERSPECTIVE - NORTHEAST



3 INTERIOR KITCHEN VIEW

**JURISDICTION:**  
JEFFERSON CO.

**ZONING:**


**HEIGHT RESTRICTIONS:**

**SETBACKS:**  
20'-0" FRONT SETBACK  
10'-0" SIDE SETBACKS  
15'-0" REAR SETBACK


**FOR CLIMATE ZONE 13 PER 2009 IRC ?**

MAXIMUM GLAZING U-FACTOR .35  
CEILING R-38  
WALLS R-21  
FLOORS R-38  
BASEMENT WALLS R-19  
SLAB PERIMETER R-VALUE & DEPTH R-9, 4 FT.  
CRAWL SPACE WALLS R-21

**CODE INFORMATION**  
1/2" = 1'-0"



**DRAWING SYMBOL LEGEND**



**DRAWING SYMBOL LEGEND**

OVERALL WINDOW SCHEDULE						
TYPE MARK	TYPE	WIDTH	HEIGHT	COUNT	Sill Height	Head Height
A	Fixed 10' x 9'	9' - 0"	9' - 0"	1	-8"	8' - 4"
B	Casement 60" x 60"	5' - 0"	5' - 0"	4	3' - 0"	8' - 0"
C	Casement 20" x 60" dark	1' - 8"	5' - 0"	3	2' - 0"	7' - 0"
D	Casement 60" x 20" dark	5' - 0"	1' - 8"	3		
E	Casement 30" x 80" dark	2' - 6"	6' - 8"	9		
F	8' x 8'	8' - 0"	8' - 0"	2	2' - 0"	10' - 0"
G	Casement 80" x 30" dark	6' - 8"	2' - 6"	1	5' - 2"	7' - 8"
H	Fixed 10' x 7'h	10' - 0"	7' - 0"	1	1' - 0"	8' - 0"
I	Casement 40" x 20" dark	3' - 4"	1' - 8"	1	5' - 0"	6' - 8"


Grand total: 25

OVERALL DOOR SCHEDULE				
CONSTRUCTION TYPE	WIDTH	HEIGHT	COMMENTS	COUNT
10' X 8' OVERHEAD GARAGE DOOR	10' - 0"	8' - 0"		2
245	2' - 6"	8' - 0"		2
2080	2' - 0"	8' - 0"		3
2680 PCKT	2' - 6"	8' - 0"		1
3080	3' - 0"	8' - 0"		9
3080 GLASS	3' - 0"	8' - 0"		1
3080 PCKT	3' - 0"	8' - 0"		3
6068	6' - 0"	8' - 0"		2
6080 GLASS	8' - 0"	8' - 0"		2
10080 GLASS	10' - 0"	8' - 0"		2


Grand total: 27

DRAWING LIST	
NO.	NAME
A0	COVER
A0.1	GENERAL ARCHITECTURAL NOTES
A1	SITE PLAN
A2	MAIN FLOOR PLAN
A3	UPPER FLOOR PLAN
A4	ROOF PLAN
A5	NORTH AND SOUTH ELEVATIONS
A6	EAST AND WEST ELEVATIONS
A7	BUILDING SECTIONS
A8	BUILDING SECTIONS
A9	BUILDING SECTIONS
A10	WALL SECTIONS AND DETAILS
A11	MAIN FLOOR REFLECTED CEILING PLAN
A12	UPPER FLOOR REFLECTED CEILING PLAN
A13	DETAILS AND INTERIOR ELEVATIONS
A14	EXTERIOR PERSPECTIVES
A15	INTERIOR PERSPECTIVES
E1	MAIN FLOOR PLAN - CONCEPTUAL ELECTRICAL PLANS
E2	UPPER FLOOR PLAN - CONCEPTUAL ELECTRICAL PLANS
S0	STRUCTURAL GENERAL NOTES AND COMMON DETAILS
S1	FOUNDATION PLAN
S1.1	3D - FOUNDATION VIEW
S2	MAIN FLOOR FRAMING PLAN
S2.1	3D - MAIN FLOOR FRAMING VIEW
S3	UPPER FLOOR FRAMING PLAN
S3.1	3D - UPPER FLOOR FRAMING VIEW
S4	ROOF FRAMING PLAN
S4.1	3D - ROOF FRAMING VIEW

AREA SCHEDULE	
NAME	AREA
MAIN FLOOR AREA	2808 SF
UPPER FLOOR AREA	2328 SF
PATIO	758 SF
GARAGE	672 SF
BALCONY	483 SF
PORCH	120 SF
Grand total:	7169 SF



4 MAIN FLOOR AREA PLAN  
1" = 10'-0"



5 UPPER FLOOR AREA PLAN  
1" = 10'-0"

**Designer**  
F9 Productions Inc.  
703 3rd Avenue Suite #D  
Longmont, CO 80501  
p 303.775.7406  
f 303.658.9846  
e lmc@f9productions.com  
contact Lance Cayko

**Owner**  
Name  
Address  
City/State  
p  
f  
e  
contact

NOT FOR CONSTRUCTION

**FRONT RANGE COMMUNITY COLLEGE**



**GRATTAROLA RESIDENCE**  
3645 W 112th Ave  
Westminster, Colorado 80031

**FRONT RANGE COMMUNITY COLLEGE**




NOT FOR CONSTRUCTION





GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE



1 SITE PLAN  
1" = 30'-0"



1

2

3

4

5

6

7

8

9

10

11

12

13

14

15


A2

MAIN FLOOR WINDOW SCHEDULE							
TYPE MARK	Count	TYPE	WIDTH	HEIGHT	SILL HEIGHT	HEAD HEIGHT	COMMENTS
B	1	Casement 60" x 60"	5' - 0"	5' - 0"	3' - 0"	8' - 0"	
D	1	Casement 60" x 20" dark	5' - 0"	1' - 8"	4' - 6"	6' - 2"	
E	6	Casement 30" x 80" dark	2' - 6"	6' - 8"	2' - 0"	8' - 8"	
F	1	8' x 8'	8' - 0"	8' - 0"	2' - 0"	10' - 0"	
G	1	Casement 80" x 30" dark	6' - 8"	2' - 6"	5' - 2"	7' - 8"	
I	1	Casement 40" x 20" dark	3' - 4"	1' - 8"	5' - 0"	6' - 8"	


Grand total: 11

MAIN FLOOR DOOR SCHEDULE					
CONSTRUCTION TYPE	Count	TYPE	WIDTH	HEIGHT	COMMENTS
245	2	36" x 96" black and glass	2' - 6"	8' - 0"	
2080	1	24" x 96" black	2' - 0"	8' - 0"	
2680 PKCT	1	2680 Pocket	2' - 6"	8' - 0"	
3080	4		3' - 0"	8' - 0"	
3080 PKCT	1	3080 Pocket	3' - 0"	8' - 0"	
6080 GLASS	1	36" x 96" black and glass	3' - 0"	8' - 0"	
10080 GLASS	2	Door_SL-10_NanaWall	10' - 0"	8' - 0"	

Grand total: 12



1 MAIN FLOOR PLAN - NEW  
1/4" = 1'-0"



2 MAIN FLOOR PLAN - MASTER BATHROOM  
1/2" = 1'-0"

NOT FOR CONSTRUCTION



GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE

A2

MAIN FLOOR PLAN

5/4/2021 8:14:39 PM

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

A3

NOT FOR CONSTRUCTION



GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031


FRONT RANGE COMMUNITY COLLEGE

A3


UPPER FLOOR PLAN

UPPER FLOOR WINDOW SCHEDULE						
TYPE MARK	TYPE	WIDTH	HEIGHT	SILL HEIGHT	HEAD HEIGHT	COMMENTS
A	Fixed 10' x 9'	9' - 0"	9' - 0"	-8"	8' - 4"	
B	Casement 60" x 60"	5' - 0"	5' - 0"	3' - 0"	8' - 0"	
C	Casement 20" x 60" dark	1' - 8"	5' - 0"	2' - 0"	7' - 0"	
D	Casement 60" x 20" dark	5' - 0"	1' - 8"			
E	Casement 30" x 80" dark	2' - 6"	6' - 8"	2' - 6"	9' - 2"	
F	8' x 8'	8' - 0"	8' - 0"	2' - 0"	10' - 0"	
H	Fixed 10' x 7'h	10' - 0"	7' - 0"	1' - 0"	8' - 0"	
Grand total: 14						

UPPER FLOOR DOOR SCHEDULE					
CONSTRUCTION TYPE	Count	TYPE	WIDTH	HEIGHT	COMMENTS
2080	2	24" x 96" black	2' - 0"	8' - 0"	
3080	5	36" x 96" BLACK	3' - 0"	8' - 0"	
3080 GLASS	1	36" x 96" BLACK-GLASS	3' - 0"	8' - 0"	
3080 PKT	2	3080 Pocket	3' - 0"	8' - 0"	
6068	2	72" x 80"	6' - 0"	8' - 0"	
6080 GLASS	1	68" x 96" BLACK	5' - 8"	8' - 0"	
Grand total: 13					



1 UPPER FLOOR PLAN - NEW  
1/4" = 1'-0"



5/4/2021 8:14:40 PM

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

A4

NOT FOR CONSTRUCTION




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031


FRONT RANGE COMMUNITY COLLEGE

A4

ROOF PLAN



1 ROOF PLAN - NEW  
1/4" = 1'-0"



5/4/2021 8:14:42 PM

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

A5

NOT FOR CONSTRUCTION

FRONT RANGE COMMUNITY COLLEGE




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE

A5

NORTH AND SOUTH ELEVATIONS



5/4/2021 8:14:47 PM


NOT FOR CONSTRUCTION



GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031


FRONT RANGE COMMUNITY COLLEGE

A  
B  
C  
D  
E



1 EAST ELEVATION  
1/4" = 1'-0"

F  
G  
H  
I  
J  
K



2 WEST ELEVATION  
1/4" = 1'-0"




NOT FOR CONSTRUCTION




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE



SECTION THROUGH STAIRS LOOKING NORTH  
1/4" = 1'-0"



SECTION THROUGH STAIRS LOOKING SOUTH  
1/4" = 1'-0"

5/4/2021 8:14:56 PM


NOT FOR CONSTRUCTION

FRONT RANGE COMMUNITY COLLEGE




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE



E SECTION LOOKING EAST THROUGH MASTER SUITE AND STAIRS  
1/4" = 1'-0"



F SECTION LOOKING WEST THROUGH GARAGE, KITCHEN, LIVING ROOM  
1/4" = 1'-0"


5/4/2021 8:14:57 PM

NOT FOR CONSTRUCTION




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE



SECTION LOOKING EAST THROUGH MASTER SUITE AND STAIRS  
1/4" = 1'-0"



SECTION THROUGH GARAGE LOOKING NORTH  
1/4" = 1'-0"


NOT FOR CONSTRUCTION




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE


A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K




1 TYPICAL WALL SECTION NORTH GARAGE WALL  
1/2" = 1'-0"



2 TYPICAL WALL SECTION EAST STAIR WALL  
1/2" = 1'-0"



3 TYPICAL WALL SECTION SOUTH FRONT DOOR WALL  
1/2" = 1'-0"



4 TYPICAL WALL SECTION WEST LIVING ROOM WALL  
1/2" = 1'-0"


1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

A11


MAIN FLOOR CEILING MATERIAL TAKEOFF	
NAME	AREA
Ceiling - 5/8" Gypsum Wall Board	2402 SF

NOTE: All heights are measured from the top of structural subfloor to the finished height of the gypsum ceilings

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K



1 MAIN FLOOR - REFLECTED CEILING PLAN  
1/4" = 1'-0"



NOT FOR CONSTRUCTION



GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE

A11

5/4/2021 8:15:01 PM

UPPER FLOOR CEILING MATERIAL TAKEOFF	
NAME	AREA
Ceiling - 1x4 T&G Dark wood	285 SF
Ceiling - 5/8" Gypsum Wall Board	2563 SF


NOT FOR CONSTRUCTION




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE

NOTE: All heights are measured from the top of structural subfloor to the finished height of the gypsum ceilings



UPPER FLOOR - REFLECTED CEILING PLAN  
1/4" = 1'-0"



5/4/2021 8:15:02 PM


NOT FOR CONSTRUCTION




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE


A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K




1 STAIRS  
1/2" = 1'-0"




2 FIREPLACE ELEVATION  
1/2" = 1'-0"



3 KITCHEN NORTH VIEW  
1/2" = 1'-0"



4 KITCHEN SOUTH VIEW  
1/2" = 1'-0"



5 KITCHEN WEST VIEW  
1/2" = 1'-0"

5/4/2021 8:15:02 PM

NOTE: All 3D view are conceptual only and are not intended to be used for construction purposes

A

B

C

D

E

F

G

H

I

J

K



NOT FOR CONSTRUCTION



GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE



NOTE: All 3D view are conceptual only and are not intended to be used for construction purposes

A



B



C



E



F


G

H



I

J



K


NOT FOR CONSTRUCTION




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE


A



B



C



D



E

MAIN FLOOR ELECTRICAL FIXTURE SCHEDULE		
FAMILY	TYPE	COUNT
Ceiling Fan - Modern	White 42"	2
Exhaust Fan - Ceiling	Exhaust Fan - Ceiling	4
Outlet-220 Single	Single	4
Outlet-Duplex	Single	48
Smoke Detector	Smoke Detector	5
Switch-Single	Single	33

F

MAIN FLOOR LIGHTING FIXTURE SCHEDULE		
FAMILY	TYPE	COUNT
Ceiling Light - Flat Round	60W - 120V	2
Downlight - Fluorescent Strip	48"	2
Downlight - Recessed Can	6" 100 watt Incandescent	29
Downlight - Strip		3
Downlight - Wet Location	6" 60 watt Incandescent	2
Entourage - Glo-Ball Floor Lamp	Entourage - Glo-Ball Floor Lamp	1
Exterior Light	120V 2	5
Floor_light_perfect_for_exterior_16733	100mm Light + 20mm Border	4
Pendant Light - Cylinder Pendant C	Pendant Light - Cylinder Pendant C	3
Pendant Light - Quadruple Cube Pendant	Pendant Light - Quadruple Cube Pendant	1
Vanity-wall_mounted	White	2
Wall_Light_15611	25 Watt	2


G

H


I

J

K



MAIN FLOOR PLAN - CONCEPTUAL ELECTRICAL  
1/4" = 1'-0"



MAIN FLOOR PLAN - CONCEPTUAL ELECTRICAL PLANS

NOT FOR CONSTRUCTION


FRONT RANGE COMMUNITY COLLEGE




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE


A



B



C



D



ELECTRICAL LEGEND  
1/2" = 1'-0"

E

UPPER FLOOR ELECTRICAL FIXTURE SCHEDULE		
FAMILY	TYPE	COUNT
Ceiling Fan - Modern	White 42"	3
Exhaust Fan - Ceiling	Exhaust Fan - Ceiling	2
Outlet-Duplex		32
Smoke Detector	Smoke Detector	6
Switch-Single	Single	22

F

UPPER FLOOR LIGHTING FIXTURE SCHEDULE		
FAMILY	TYPE	COUNT
Ceiling - Flat Round	100 Watt - Incandescent	1
Downlight - Recessed Can	6" 100 watt Incandescent	14
Downlight - Wet Location	6" 60 watt Incandescent	2
Exterior Light	120V 2	2
Vanity-wall_mounted	White	3


G

H


I

J

K



UPPER FLOOR PLAN - CONCEPTUAL ELECTRICAL  
1/4" = 1'-0"



SCALE: 1" = 30'-0"

UPPER FLOOR PLAN - CONCEPTUAL ELECTRICAL PLANS

FOUNDATION RELATED EARTHWORK

EXCAVATION

- 1. EXCAVATE SUBSOIL TO ACCOMMODATE NEW FOUNDATION TO DEPTH SHOWN ON DRAWINGS. HAND TRIM EXCAVATIONS. REMOVE LOOSE MATERIAL.
2. NOTIFY GEOTECHNICAL ENGINEER A MINIMUM OF 72 HOURS PRIOR TO EXCAVATIONS AND DRILLED PIER INSTALLATION TO SCHEDULE A REVIEW OF NATIVE SOIL CONDITIONS.
3. PROTECT THE SITE AND ALL CONSTRUCTION, EXISTING AND PROPOSED, FROM THE EFFECTS OF FREEZING OR FROST ACTION. SUBMITTALS FOR REVIEW:

- 1. SUBMIT SIEVE ANALYSIS AND STANDARD MOISTURE-DENSITY CURVE FOR EACH BACKFILL MATERIAL. RESUBMIT WHENEVER A NEW PIT OR SUBSTANTIALLY DIFFERENT MATERIAL IS USED.

BACKFILL AND COMPACTION

- 1. PLACE AND COMPACT BACKFILL IN EQUAL CONTINUOUS LAYERS NOT EXCEEDING 8" OF COMPACTED DEPTH FOR HAND HELD COMPACTION EQUIPMENT AND A MAXIMUM OF 12" INCHES COMPACTED DEPTH FOR VIBRATORY ROLLERS.
2. MAINTAIN OPTIMUM MOISTURE CONTENT OF BACKFILL MATERIALS TO ATTAIN COMPACTION DENSITY.
3. BACKFILL SIMULTANEOUSLY ON EACH SIDE OF FOUNDATION WALLS THAT ARE NOT DESIGNED FOR RETAINING SOIL ON ONE SIDE.
4. DO NOT BACKFILL CONCRETE WALLS UNTIL FLOOR FRAMING SUPPORTING TOP OF WALLS IS IN PLACE.
5. COMPACTION TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D2922, TEST METHODS FOR SOIL BY NUCLEAR METHODS. MAXIMUM DENSITY SHALL BE DETERMINED BY THE MODIFIED PROCTOR METHOD, ASTM D1557.

BACKFILL REQUIREMENTS:

- 1. FILL WITHIN BUILDING ENVELOPE:
a. MATERIAL: GRANULAR BACKFILL
b. COMPACTION: 95% MODIFIED PROCTOR
c. TESTING: EVERY OTHER LIFT, EVERY 1000 SF
2. BACKFILL ALONG EXTERIOR OF BUILDING AT FROST WALLS:
a. MATERIAL: SUITABLE NATIVE SOIL
b. COMPACTION: 90% MODIFIED PROCTOR
3. GRAVEL BELOW SLABS:
a. MATERIAL: CRUSHED GRAVEL, GRANULAR BACKFILL
b. COMPACTION: 95% MODIFIED PROCTOR
c. TESTING: EVERY 1000 SF

MATERIALS:

Table with columns: SIEVE DESIGNATION, % BY WEIGHT PASSING SIEVES. Rows include 3 INCH, NO. 4, NO. 100, NO. 200.

Table with columns: SIEVE DESIGNATION, % BY WEIGHT PASSING SIEVES. Rows include 2 INCH, 1 1/2 INCH, NO. 4, NO. 100, NO. 200.

Table with columns: SIEVE DESIGNATION, % WEIGHT BY PASSING SIEVES. Rows include 1 INCH, 3/8 INCH, 1/4 INCH, 3/8 INCH, No. 4, No. 5.

- 4. SUITABLE NATIVE SOIL: ON SITE SAND OR GRAVEL REASONABLY FREE OF LOAM, SILT, CLAY, OR ORGANIC MATTER.

CAST-IN-PLACE CONCRETE

- 1. CODES AND STANDARDS: COMPLY WITH THE PROVISIONS OF THE LATEST EDITIONS OF:
a. ACI 318 "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE"
b. ACI 301 "SPECIFICATIONS FOR STRUCTURAL CONCRETE"
c. ACI 305 "HOT WEATHER CONCRETING"
d. ACI 306 "STANDARD SPECIFICATION FOR COLD WEATHER CONCRETING"
e. ACI 308 "STANDARD PRACTICE FOR CURING CONCRETE".
2. PRIOR TO PLACEMENT OF CONCRETE, SUBMIT TO ENGINEER MIX DESIGN INCLUDING TECHNICAL DATA SHEETS ON ANY ADMIXTURES TO BE USED.
3. OMITTED
a. OMITTED
b. OMITTED
c. OMITTED
d. OMITTED
5. SUBMIT MIX DESIGN AND EITHER TRIAL MIX DESIGNS OR HISTORIC FIELD DATA FOR APPROVAL IN ACCORDANCE WITH ACI 318, CHAPTER 5.
6. COMPRESSIVE STRENGTH AT 28 DAYS:
a. FOUNDATION WALLS AND FOOTINGS, INTERIOR SLABS: 3000 PSI
b. EXTERIOR SLABS: 4000 PSI
8. TRANSIT MIX SHALL CONFORM TO ASTM C94.
9. MINIMUM CEMENT CONTENT FOR 3000 PSI CONCRETE IS 517 POUNDS PER CUBIC YARD.
10. MINIMUM CEMENT CONTENT FOR 4000 PSI CONCRETE IS 564 POUNDS PER CUBIC YARD.
11. MAXIMUM AGGREGATE SIZE SHALL BE 3/4".
12. SLUMP: 3" TO 5".
13. AIR ENTRAINMENT OF 4 TO 6% BY VOLUME. DO NOT ADD AIR ENTRAINING ADMIXTURES FOR INTERIOR SLABS ON GRADE.
14. NO CHLORIDE OR OTHER UNAUTHORIZED ADMIXTURES SHALL BE USED.
15. PLACE NO CONCRETE WHEN AMBIENT TEMPERATURE IS BELOW 40 DEGREES FAHRENHEIT OR MORE THAN 90 DEGREES FAHRENHEIT UNLESS PLACEMENT PROCEDURE IS IN COMPLIANCE WITH ACI 305 OR ACI 306.
4. COMPLY WITH ACI CODES AND PLACE CONCRETE IN A CONTINUOUS OPERATION WITHIN PLANNED JOINTS OR SECTIONS. DO NOT PERMIT COLD JOINTS TO OCCUR.

- 1. CURING: BEGIN INITIAL CURING AS SOON AS FREE WATER HAS DISAPPEARED FROM EXPOSED SURFACES. WHERE POSSIBLE, KEEP CONTINUOUSLY WET FOR 72 HOURS. CONTINUE CURING BY USE OF MOISTURE RETAINING COVER OR MEMBRANE-FORMING CURING COMPOUND.
2. GROUT: PRE-MIXED, NON-SHRINK, WITH MINIMUM COMPRESSIVE STRENGTH OF 7000 PSI AT 28 DAYS AS MANUFACTURED BY FIVE STAR PRODUCTS, INC., OR APPROVED EQUIVALENT.
3. NO CONCRETE SHALL BE DROPPED MORE THAN 4 FEET INSIDE A FORM.

GENERAL STRUCTURAL NOTES

1/4" = 1'-0"

CONCRETE FORMWORK

- 1. CONCRETE FORMS SHALL BE CLEAN AND FREE FROM DEBRIS. IF FORMS ARE COATED WITH A RELEASE AGENT, THE RELEASE AGENT SHALL BE COLORLESS MINERAL OIL WHICH SHALL NOT STAIN CONCRETE OR ABSORB MOISTURE OR IMPAIR NATURAL BONDING OF CONCRETE.
2. SOAK INSIDE SURFACE OF UNTREATED FORMWORK WITH WATER PRIOR TO USE.
3. DO NOT DAMAGE CONCRETE DURING FORM STRIPPING.
4. OBTAIN APPROVAL BEFORE FRAMING OPENINGS IN STRUCTURAL MEMBERS WHICH ARE NOT INDICATED ON DRAWINGS.
5. PROVIDE BRACING TO ENSURE STABILITY OF FORMWORK.
6. DO NOT REMOVE FORMS OR BRACING UNTIL CONCRETE HAS GAINED SUFFICIENT STRENGTH TO CARRY ITS OWN WEIGHT AND IMPOSED LOADS.
7. UNLESS OTHERWISE NOTED, CENTER ALL FOUNDATION PIERS AND FOOTINGS ON COLUMN CENTERLINES.

CONCRETE REINFORCING

- 1. REINFORCING STEEL SHALL BE ASTM A615, 60 KSI YIELD GRADE, DEFORMED STEEL BARS PER ASTM A305.
2. LAP HORIZONTAL BARS 30 BAR DIAMETERS UNLESS NOTED OTHERWISE.
3. WELDED STEEL WIRE FABRIC SHALL BE ASTM A185. LAP A MINIMUM OF ONE MESH.
4. CHAIRS AND SPACERS SHALL BE PLACED TO ADEQUATELY SUPPORT REINFORCING DURING PLACEMENT. FOREIGN MATERIALS SUCH AS WOOD OR OTHER UNSUITABLE SUPPORTS SHALL NOT BE USED TO SUPPORT REINFORCING. SET WIRE TIES SO ENDS ARE DIRECTED INTO CONCRETE WHERE CONCRETE WILL BE EXPOSED.
5. CONCRETE CLEAR COVER FOR REINFORCEMENT (UNLESS SHOWN OTHERWISE):
a. BOTTOM OF FOOTINGS AND SLABS ON GRADE: 3".
b. FOUNDATION WALLS AND EXTERIOR WALLS: 2".
c. TOP AND BOTTOM OF ELEVATED SLABS: 3/4".
d. ALL FACES OF PIERS: 1-1/2".

RELATED ITEMS

- 1. OMITTED

STRUCTURAL STEEL

SUBMITTALS FOR REVIEW

- 1. SHOP DRAWINGS: INDICATE PROFILES, SIZES, SPACING, LOCATIONS OF STRUCTURAL MEMBERS, DECKING, OPENINGS, ATTACHMENTS, AND FASTENERS. SHOW ALL CONNECTION DETAILS. PROVIDE DESIGN OF CONNECTIONS NOT DETAILED ON DRAWINGS. INDICATE WELDED CONNECTIONS WITH AWS A2.0 WELDING SYMBOLS. INDICATE NET WELD LENGTHS.

SUBMITTALS FOR INFORMATION

- 1. MANUFACTURER'S MILL CERTIFICATE: CERTIFY THAT PRODUCTS MEET OR EXCEED SPECIFIED REQUIREMENTS.
2. MILL TEST REPORTS: SUBMIT INDICATING STRUCTURAL STRENGTH, DESTRUCTIVE AND NON-DESTRUCTIVE TEST ANALYSIS.
3. WELDERS CERTIFICATES: CERTIFY WELDERS EMPLOYED ON THE WORK, VERIFYING AWS QUALIFICATION WITHIN THE PREVIOUS 12 MONTHS.

QUALITY ASSURANCE

- 1. FABRICATE STRUCTURAL STEEL MEMBERS IN ACCORDANCE WITH AISC CODE OF STANDARD PRACTICE.
2. PERFORM WORK IN ACCORDANCE WITH AISC SECTION 10.
3. FABRICATOR AND ERECTOR: COMPANY SPECIALIZING IN PERFORMING THE WORK OF THIS SECTION WITH MINIMUM FIVE YEARS EXPERIENCE.

MATERIALS

- 1. STRUCTURAL STEEL WIDE FLANGE MEMBERS: ASTM A992/A572, GRADE 50
2. ANGLES, CHANNELS, PLATE AND OTHER HOT ROLLED SHAPES: ASTM A36
3. STRUCTURAL TUBING: ASTM A500, GRADE B.
4. PIPE COLUMNS: ASTM A53 GRADE B.
5. BOLTS, NUTS, AND WASHERS: MINIMUM 3/4" DIAMETER ASTM A325 BOLTS, ASTM A563 NUTS WITH HARDENED WASHERS, GALVANIZED TO ASTM A153 FOR GALVANIZED STRUCTURAL MEMBERS. ASTM A490 BOLTS REQUIRED WHERE NOTED ON DRAWINGS.
6. ANCHOR BOLTS: ASTM A-307 FOR HEADED BOLT ASTM A-36 FOR THREADED ROD
7. WELDING MATERIALS: AWS D1.1; TYPE REQUIRED FOR MATERIALS BEING WELDED.
8. GROUT: NON-SHRINK TYPE, PRE-MIXED COMPOUND CONSISTING OF NON-METALLIC AGGREGATE CEMENT, WATER REDUCING AND PLASTICIZING ADDITIVES, CAPABLE OF DEVELOPING A MINIMUM COMPRESSIVE STRENGTH OF 7,000 PSI AT 28 DAYS AS MANUFACTURED BY FIVE STAR PRODUCTS, INC., FAIRFIELD, CT, OR APPROVED EQUIVALENT.
9. SHOP AND TOUCH-UP PRIMER: TNEMEC SERIES FM88 OR APPROVED EQUIVALENT.
10. TOUCH-UP PRIMER FOR GALVANIZED SURFACES: TNEMEC SERIES 37, ZINC RICH RED APPROVED EQUIVALENT.

FINISH

- 1. PREPARE STRUCTURAL COMPONENT SURFACES IN ACCORDANCE WITH SSPC SP-2 FOR ENCLOSED STEEL TO RECEIVE STANDARD PRIMER AND SSPC SP-6 FOR EXPOSED STEEL.
2. SHOP PRIME STRUCTURAL STEEL MEMBERS. DO NOT PRIME SURFACES THAT WILL BE EXPOSED, FIREPROOFED, FIELD WELDED OR IN CONTACT WITH CONCRETE.
3. PRIME AND PAINT ARCHITECTURALLY EXPOSED STEEL AFTER INSTALLATION.
4. WHERE INDICATED, STRUCTURAL STEEL MEMBERS ARE TO BE GALVANIZED IN ACCORDANCE WITH ASTM A123. PROVIDE MINIMUM 1.25 OZ/SQ FT GALVANIZED COATING.

ERECTION

- 1. ALLOW FOR ERECTION LOADS, AND FOR SUFFICIENT TEMPORARY BRACING TO MAINTAIN STRUCTURE SAFE, PLUMB, AND IN TRUE ALIGNMENT UNTIL COMPLETION OF ERECTION AND INSTALLATION OF PERMANENT BRACING.
2. FIELD WELD COMPONENTS INDICATED ON DRAWINGS AND SHOP DRAWINGS.
3. DO NOT FIELD CUT OR ALTER STRUCTURAL MEMBERS WITHOUT APPROVAL OF ARCHITECT/ENGINEER.
4. AFTER ERECTION, PRIME WELDS, ABRASIONS, AND SURFACES NOT SHOP PRIMED, EXCEPT SURFACES TO BE IN CONTACT WITH CONCRETE.
5. GROUT UNDER BASE PLATES

WOOD FRAMING AND SHEATHING GENERAL

- 1. UNLESS OTHERWISE SPECIFIED, EACH PIECE OF LUMBER SHALL BEAR THE GRADE MARK, STAMP, OR OTHER IDENTIFYING MARKS INDICATING GRADES OF MATERIAL, AND RULES OR STANDARDS UNDER WHICH PRODUCED, SUCH IDENTIFYING MARKS ON A MATERIAL SHALL BE IN ACCORDANCE WITH THE RULE OR STANDARD UNDER WHICH MATERIAL IS PRODUCED, INCLUDING REQUIREMENTS FOR QUALIFICATIONS AND AUTHORITY OF THE INSPECTION ORGANIZATION. USAGE OF AUTHORIZED IDENTIFICATION, AND INFORMATION INCLUDED IN THE IDENTIFICATION. THE INSPECTION AGENCY FOR LUMBER SHALL BE APPROVED BY THE BOARD OF REVIEW, AMERICAN LUMBER STANDARDS COMMITTEE, TO GRADE SPECIES USED.

- 2. PROTECT LUMBER AND OTHER PRODUCTS FROM DAMPNESS BOTH DURING AND AFTER DELIVERY AT THE SITE. PILE SHEATHING AND LUMBER IN STACKS IN SUCH A MANNER AS TO PROVIDE ADEQUATE AIR CIRCULATION AND TO PREVENT WARPING. LOCATE STACKS IN WELL DRAINED AREAS, SUPPORTED AT LEAST SIX INCHES ABOVE GRADE AND COVER TO PROTECT LUMBER FROM RAIN, SNOW AND DRIVING RAIN.
3. STORE SEASONED MATERIALS IN DRY PORTIONS OF BUILDING.
4. PROTECT SHEET MATERIALS FROM CORNERS BREAKING AND DAMAGING SURFACES WHILE UNLOADING.
5. NOMINAL SIZES ARE INDICATED EXCEPT AS SHOWN BY DETAIL DIMENSIONS. PROVIDE ACTUAL SIZES AS REQUIRED BY PRODUCT STANDARD 20, DEPARTMENT OF COMMERCE.
6. MAXIMUM MOISTURE CONTENT SHALL NOT EXCEED 19%.

MATERIALS

- 1. 2X6 AND 2X4 BEARING WALLS, INTERIOR AND EXTERIOR LOCATIONS: DOUGLAS FIR-LARCH NO.2 AS GRADED BY WWPA
2. STRUCTURAL ROOF AND FLOOR FRAMING: NO.2 AS GRADED BY WWPA
3. PRESERVATIVE PRESSURE TREATED LUMBER: SOUTHERN PINE NO. 2, AS GRADED BY SPIB
4. LAMINATED VENEER LUMBER (LVL):
a. PROVIDE LVL HEADERS AND BEAMS AS INDICATED.
b. LVL FRAMING SHALL BE LAMINATED DOUGLAS FIR OR SOUTHERN PINE (GP LAM BY GEORGIA PACIFIC OR MICROLAM BY TRUS-JOIST OR EQUIVALENT) MEETING THE FOLLOWING MINIMUM ALLOWABLE STRESS CRITERIA:
FB (BENDING STRESS) = 2600 PSI
FV (HORIZ. SHEAR STRESS) = 285 PSI
E (MODULUS OF ELASTICITY) = 1,900,000 PSI
FC (COMPRESSION PERPENDICULAR TO GRAIN) = 750 PSI
6. PARALLEL STRAND LUMBER (PSL):
a. PROVIDE PSL BEAMS AND POSTS AS INDICATED.
b. PSL FRAMING (PARALLAM BY TRUS-JOIST OR EQUIVALENT) TO MEET THE FOLLOWING MINIMUM ALLOWABLE STRESS CRITERIA:
FB (BENDING STRESS) = 2900 PSI
FV (HORIZ. SHEAR STRESS) = 290 PSI
E (MODULUS OF ELASTICITY) = 2,000,000 PSI
FC (COMPRESSION PERPENDICULAR TO GRAIN) = 750 PSI

- 7. PREFABRICATED WOOD I-JOISTS (TJI):
a. PROVIDE TJI JOISTS AS INDICATED ON DRAWINGS.
b. I-JOISTS SHALL BE TJIS AS MANUFACTURED BY TRUS-JOIST OR APPROVED EQUIVALENT.
8. MISCELLANEOUS LUMBER: PROVIDE WOOD FOR SUPPORT OR ATTACHMENT OF THE WORK INCLUDING NON-BEARING PARTITIONS, CANT STRIPS, BUCKS, NAILERS, BLOCKING, FURRING, GROUNDS, STRIPPING AND SIMILAR MEMBERS. PROVIDE LUMBER OF SIZES AND SHAPES INDICATED. GRADE: HEM-FIR STUD GRADE AS GRADED BY WWPA.
9. ROOF, FLOOR AND WALL SHEATHING: APA RATED OR ADVANTECH VIP+ SHEATHING, THICKNESS AS INDICATED, SPAN RATING AS REQUIRED TO SUIT SUPPORT SPACING INDICATED, EXPOSURE DURABILITY 1, THREE SPAN MINIMUM.
10. FASTENERS AND ANCHORS: FURNISH ITEMS OF ROUGH HARDWARE, METAL CONNECTORS, BOLTS, ETC., REQUIRED TO COMPLETE THE WORK. BOLTS, NUTS AND WASHERS SHALL BE HOT DIPPED ELECTRO GALVANIZED STEEL. FASTENERS AND ANCHORS IN CONTACT WITH PRESSURE TREATED LUMBER SHALL BE STAINLESS STEEL OR STEEL HOT DIP GALVANIZED TO G-185.
11. WOOD CONNECTORS SHALL BE BY SIMPSON STONG-TIE OR APPROVED EQUIVALENT. SIMPSON STRONG-TIE CONNECTORS SHALL CONFORM TO MANUFACTURER'S COATING RECOMMENDATIONS. UNLESS OTHERWISE NOTED ON DRAWINGS, USE THE FOLLOWING CONNECTORS:
a. TJI JOISTS: IUS HANGERS.
b. 2x JOISTS: LUS HANGERS.
c. POST BASES: AB OR ABU POST BASES.
d. POST CAPS: AC AND ACE POST CAPS.
LVL BEAMS: HU AND HUC BEAM HANGERS.
12. SUBFLOOR GLUE: APA AFG-01, WATERPROOF OF WATER SOLVENT BASE, AIR CURE TYPE, CARTRIDGE DISPENSED.

- 13. WOOD PRESERVATIVE (PRESSURE TREATMENT): AWWPA TREATMENT ACQ USING WATER BORNE PRESERVATIVE WITH 0.40 PERCENT RETAINAGE.

EXECUTION

- 1. SET STRUCTURAL MEMBERS LEVEL AND PLUMB, IN CORRECT POSITION.
2. MAKE PROVISIONS FOR ERECTION LOADS, AND FOR SUFFICIENT TEMPORARY BRACING TO MAINTAIN STRUCTURE SAFE, PLUMB, AND IN TRUE ALIGNMENT UNTIL COMPLETION OF ERECTION AND INSTALLATION OF PERMANENT BRACING.
3. PLACE HORIZONTAL MEMBERS, CROWN SIDE UP.
4. CONSTRUCT LOAD BEARING FRAMING AND CURB MEMBERS FULL LENGTH WITHOUT SPLICES.
5. DOUBLE MEMBERS AT OPENINGS OVER 24 INCHES WIDE. SPACE SHORT STUDS OVER AND UNDER OPENING TO STUD SPACING.
6. CONSTRUCT DOUBLE JOIST HEADERS AT FLOOR AND CEILING OPENINGS AND UNDER WALL STUD PARTITIONS THAT ARE PARALLEL TO FLOOR JOISTS. FRAME RIGIDLY INTO JOISTS.
7. BRIDGE JOISTS FRAMING IN EXCESS OF 8 FEET SPAN AT MID-SPAN AND WHERE SHOWN ON DRAWINGS. FIT SOLID BLOCKING OR BRIDGING AT ENDS OF MEMBERS.
8. PLACE FULL WIDTH CONTINUOUS SILL FLASHINGS UNDER FRAMED WALLS ON CEMENTITIOUS FOUNDATIONS. LAP FLASHING JOINT 4 INCHES MINIMUM.
9. SECURE ROOF SHEATHING WITH LONGER EDGE PERPENDICULAR TO FRAMING MEMBERS AND WITH ENDS STAGGERED AND SHEET ENDS OVER BEARING.
10. USE SHEATHING CLIPS BETWEEN SHEETS BETWEEN ROOF FRAMING MEMBERS.
11. PROVIDE SOLID EDGE BLOCKING BETWEEN SHEETS.
12. WHERE TONGUE AND GROOVE PLYWOOD IS USED, FULLY ENGAGE TONGUE AND GROOVE EDGES.
13. SECURE WALL SHEATHING WITH LONG DIMENSION PERPENDICULAR TO WALL STUDS, WITH ENDS OVER FIRM BEARING AND STAGGERED.
14. SECURE SUB-FLOOR SHEATHING WITH LONGER EDGE PERPENDICULAR TO FLOOR FRAMING AND WITH END JOINTS STAGGERED AND SHEET ENDS OVER BEARING. ATTACH WITH SUB-FLOOR GLUE AND #8 SCREWS.
15. TOLERANCES:
a. FRAMING MEMBERS: 1/4 INCH FROM TRUE POSITION, MAXIMUM.
b. SURFACE FLATNESS OF FLOOR: 1/4 INCH IN 10 FEET MAXIMUM, AND 1/2 INCH IN 30 FEET MAXIMUM.
17. ALL POSTS AND COLUMNS FROM HEADERS AND BEAMS SHALL BEAR CONTINUOUSLY TO CONCRETE FOUNDATIONS INCLUDING BLOCKING IN FLOOR AND ROOF SPACES. BLOCKING SHALL BE OF THE SIZE AND SHAPE TO CARRY THE REQUIRED LOADING.
18. ALL BOTTOM BEARING PLATES, FOR STUD WALLS OR BEAM BEARING, SHALL BE ANCHORED TO THE FOUNDATION WITH 1/2" DIAMETER ANCHOR BOLTS AT 32" ON CENTER, UNLESS NOTED OTHERWISE.
19. ALL WOOD IN CONTACT WITH CONCRETE SHALL BE PRESERVATIVE PRESSURE TREATED, P.P.T.
20. ALL EXTERIOR AND INTERIOR BEARING WALLS SHALL HAVE BLOCKING SPACED AT A MAXIMUM OF 48" O.C.

PLATE CONNECTED WOOD ROOF TRUSSES

- 1. FIELD-VERIFY EXISTING TRUSS PROFILES AND DIMENSIONS PRIOR TO FABRICATION OF NEW TRUSSES.
2. DESIGN NEW TRUSSES USING DESIGN LOADS AS FOLLOWS: 30 PSF ROOF SNOW LOAD, 10 PSF TOP CHORD DEAD LOAD, 10 PSF BOTTOM CHORD DEAD LOAD.
3. DESIGN TO LOADINGS AND CONFIGURATIONS SHOWN ON DRAWINGS WITH DEFLECTION LIMITED TO 1/360 OF SPAN FOR SNOW AND CEILING LOAD.
4. SUBMIT TRUSS SHOP DRAWINGS INCLUDING LAYOUT PLANS CODED TO INDICATE TRUSS DESIGN LOCATIONS. FOR EACH TRUSS, INDICATE SIZES AND SPACING OF TRUSSES AND ASSOCIATED COMPONENTS, WEB AND CHORD SIZES, PLATE SIZES, FASTENER DESCRIPTIONS AND SPACINGS, LOADS AND TRUSS CAMBERS, AND FRAME OPENINGS. SUBMIT ALL DESIGN CALCULATIONS INCLUDING DEFLECTIONS.
5. PUBLICATIONS: SUBMIT ONE COPY OF BCSI 1-03 AND BCSI B1 SUMMARY SHEET AND PROVIDE TWO COPIES TO ERECTOR TO BE KEPT ON SITE.
6. REVIEW OF TRUSS SUBMITTALS BY THE ENGINEER SHALL BE ONLY FOR CONFORMANCE WITH THE DESIGN CONCEPT AND SHALL NOT INDICATE APPROVAL OF THE DESIGN OF THE TRUSS OR ITS COMPONENTS. REVIEW SHALL BE LIMITED TO THE FOLLOWING:
a. VERIFICATION OF CORRECT LOADING USED BY THE TRUSS ENGINEER.
b. REVIEW OF TRUSS REACTIONS AND VERIFICATION THAT BUILDING ELEMENTS ARE ADEQUATE TO SUPPORT TRUSS REACTIONS AS DETERMINED BY THE TRUSS ENG
c. REVIEW OF TRUSS DEFLECTIONS AS CALCULATED BY THE TRUSS ENGINEER FOR SUITABILITY IN THE OVERALL BUILDING CONFIGURATION.
d. DIMENSIONS WILL BE REVIEWED FOR CONFORMANCE WITH THE BEARING LOCATIONS AS INDICATED ON THE PROJECT DRAWINGS.

- DESIGN AND FABRICATE TRUSSES IN ACCORDANCE WITH TRUSS PLATE INSTITUTE TPI 1-2002.
9. TRUSS HANDLING AND INSTALLATION SHALL BE IN ACCORDANCE WITH TPI BCSI 1-03.
10. DESIGN TRUSSES UNDER DIRECT SUPERVISION OF A PROFESSIONAL ENGINEER/STRUCTURAL ENGINEER EXPERIENCED IN DESIGN OF THIS WORK AND LICENSED IN COLORADO. SHOP DRAWINGS SHALL BEAR THE STAMP OF THAT PROFESSIONAL.
11. MINIMUM TOP AND BOTTOM CHORD MEMBER SIZE SHALL BE 2x6. MINIMUM WEB MEMBER SIZE SHALL BE 2x4. MINIMUM STRESS VALUES SHALL MEET THE REQUIREMENTS OF HEM-FIR OR DOUGLAS FIR NO. 1 NO. 2, 19 PERCENT MAXIMUM AND 7 PERCENT MINIMUM MOISTURE CONTENT. STUD GRADE LUMBER SHALL NOT BE USED.
12. STEEL PLATE CONNECTORS SHALL BE ASTM A446 STEEL, GRADE B, HOT DIP GALVANIZED, DIE STAMPED WITH INTEGRAL TEETH THICKNESS AS DETERMINED BY TRUSS ENGINEER.
13. TRUSS BRIDGING: TYPE, SIZE AND SPACING RECOMMENDED BY TRUSS MANUFACTURER.
14. TRUSS ERECTOR SHALL VERIFY THAT SUPPORTS AND OPENINGS ARE READY TO RECEIVE TRUSSES PRIOR TO BEGINNING WORK.
15. MAKE PROVISIONS FOR ERECTION LOADS AND FOR SUFFICIENT TEMPORARY BRACING TO MAINTAIN STRUCTURE PLUMB AND IN TRUE ALIGNMENT UNTIL COMPLETION OF ERECTION AND INSTALLATION OF PERMANENT BRACING.
16. PERMANENT BRACING AS SHOWN ON PROJECT DRAWINGS AND AS INDICATED IN BCSI 1-03 SHALL BE COMPLETED NO LATER THAN IMMEDIATELY AFTER INSTALLATION OF TOP CHORD SHEATHING.
17. DO NOT FIELD CUT OR ALTER STRUCTURAL MEMBERS WITHOUT APPROVAL OF ARCHITECT AND STRUCTURAL ENGINEER.
18. TRUSSES SHALL BE INSTALLED A MAXIMUM OF 1/2 INCH FROM TRUE POSITION.

BASIS OF DESIGN:

BUILDING CODE: 2006 IRC

DESIGN LOADS:

ROOF DEAD LOAD: 20 PSF
FLOOR LIVE LOAD: 40 PSF
FLOOR DEAD LOAD: 20 PSF (45 PSF @ SLAB ON STEEL DECKS)
GROUND SNOW LOAD (PG): 30 PSF
ROOF SNOW LOAD: 30 PSF

WIND DESIGN DATA:
BASIC WIND SPEED: 100 MPH
EXPOSURE C

SEISMIC DESIGN CATEGORY B

FOUNDATION:
REFER TO SOILS REPORT #..... BY .....
DATED: .....

ALLOWABLE END BEARING PRESSURE: 25 KSF AND MINIMUM DEAD LOAD: 7.5 KSF, 2.5 KSF SKIN FRICTION AFTER INITIAL 3 FT. OF PENETRATION INTO BEDROCK, MINIMUM OF 9 FT. PENETRATION INTO BEDROCK, MIN. PIER LENGTH OF 29 FT.

FROST LINE DEPTH - 36"

CHECK AND FILL OUT

NOT FOR CONSTRUCTION

FRONT RANGE COMMUNITY COLLEGE



GRATTAROLA RESIDENCE
3645 W 112th Ave
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K

S1

NOT FOR CONSTRUCTION





GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE

S1

FOUNDATION PLAN



THE FOUNDATION PLAN DEPICTS:  
- FOUNDATION WALLS  
- FOUNDATION FOOTINGS  
- FOUNDATION PIERS

FRAMING LEGEND - FOUNDATION  
1/4" = 1'-0"

FOUNDATION PLAN  
1/4" = 1'-0"

A6 2

A5 2

1 A9

1 A6

1 A7  
2 A7  
A7

2 A10

1 A8

2 A9

2 A8

1 A5



SCALE: 1" = 30'-0"


5/4/2021 8:15:06 PM

NOT FOR CONSTRUCTION



GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE



1 3D - FOUNDATION ONLY

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

S2

NOT FOR CONSTRUCTION




GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE

S2


MAIN FLOOR FRAMING PLAN

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K




THE MAIN FLOOR FRAMING PLAN DEPICTS:  
- MAIN FLOOR HEADERS  
- MAIN FLOOR BOX


FRAMING LEGEND - MAIN FLOOR  
1/4" = 1'-0"



2 MAIN FLOOR FRAMING PLAN - DECK  
FRAMING  
3/16" = 1'-0"



1 MAIN FLOOR FRAMING PLAN  
1/4" = 1'-0"




5/4/2021 8:15:07 PM

NOT FOR  
CONSTRUCTION



**GRATTAROLA RESIDENCE**  
3645 W 112th Ave  
Westminster, Colorado 80031

**FRONT RANGE COMMUNITY COLLEGE**





1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K

SS



NOT FOR CONSTRUCTION



GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE


SS



THE UPPER FLOOR FRAMING PLAN DEPICTS:  
- UPPER FLOOR HEADERS  
- UPPER FLOOR BOX

FRAMING LEGEND - UPPER FLOOR  
1/4" = 1'-0"

1 UPPER FLOOR FRAMING PLAN  
1/4" = 1'-0"



UPPER FLOOR FRAMING PLAN

5/4/2021 8:15:11 PM

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

A

B

C

D

E

F


G

H

I

J

K



S3.1

NOT FOR  
CONSTRUCTION



**GRATTAROLA RESIDENCE**  
3645 W 112th Ave  
Westminster, Colorado 80031

**FRONT RANGE COMMUNITY COLLEGE**

S3.1

5/4/2021 8:15:14 PM

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

S4

NOT FOR CONSTRUCTION



GRATTAROLA RESIDENCE  
3645 W 112th Ave  
Westminster, Colorado 80031

FRONT RANGE COMMUNITY COLLEGE

S4

ROOF FRAMING PLAN

A

B

C

D

E

F


G

H

I

J

K




THE ROOF FRAMING PLAN DEPICTS:  
- ROOF FRAMING

FRAMING LEGEND - ROOF  
1/4" = 1'-0"

1 ROOF FRAMING PLAN  
1/4" = 1'-0"

5/4/2021 8:15:16 PM



SCALE: 1" = 30'-0"

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

A

B

C

D

E

F


G

H

I

J

K



S4.1

NOT FOR  
CONSTRUCTION



**GRATTAROLA RESIDENCE**  
 3645 W 112th Ave  
 Westminster, Colorado 80031

**FRONT RANGE COMMUNITY COLLEGE**

S4.1

5/4/2021 8:15:19 PM